

PROJECT: \_\_\_\_\_  
 LOCATION: \_\_\_\_\_  
 ITEM#: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_

## COMPETITOR SERIES®



C-F35-NG/LP



C-F40-NG/LP



C-F50-NG/LP



C-F75-NG/LP

## FRYERS

- Robertshaw® electro-mechanical thermostat for adjusting temperatures within a range of 200°F to 400°F
- Beautiful ergonomic design and easy to clean
- All stainless steel tank & cabinetry
- Removable basket hanger for cleaning purposes
- Auto reset high limit control for high temperatures
- Cooling zone inside the fryer tank
- Twin nickel chrome-plated wire mesh baskets with blue plastic coated handles
- Manual pilot ignition
- Built in flue deflector
- Full port drain within valve
- Four (4) standard 6" casters (2x locking)
- Migali Industries® Protection Plan: 1 Year Parts & Labor Warranty, 5 Years Oil Tank Warranty

MODEL	BURNERS	VOLUME	TOTAL BTU NG / LP	BTU PER BURNER NG / LP	IN TAKE TUBE PRESSURE (W.C.) NG / LP	NOZZLE NO. NG / LP	IGNITION	VALVE TYPE	THERMOSTAT TEMP LIMIT	TEMP LIMIT	EXTERIOR DIMENSIONS W X D X H	PACKAGED DIMENSIONS W X D X H	WEIGHT	PACKAGED WEIGHT
C-F35-NG C-F35-LP	3	35 lbs.	60,000 / 60,000	20,000 / 20,000	2 / 5	#36 / #52	Manual	Often open flame, flame protection	400° F	450° F	15.6 x 30.1 x 44.4	17.7 x 33.5 x 37.9	135 lbs.	166 lbs.
C-F40-NG C-F40-LP	3	40 lbs.	102,000 / 90,000	34,000 / 30,000	4 / 10	#36 / #52	Manual	Often open flame, flame protection	400° F	450° F	15.6 x 30.1 x 44.4	17.7 x 33.5 x 37.9	135 lbs.	166 lbs.
C-F50-NG C-F50-LP	4	50 lbs.	136,000 / 120,000	34,000 / 30,000	4 / 10	#36 / #52	Manual	Often open flame, flame protection	400° F	450° F	15.6 x 30.1 x 44.4	17.7 x 33.5 x 37.9	146 lbs.	172 lbs.
C-F75-NG C-F75-LP	5	75 lbs.	170,000 / 150,000	34,000 / 30,000	4 / 10	#36 / #52	Manual	Often open flame, flame protection	400° F	450° F	21.1 x 30.1 x 44.4	23.2 x 33.5 x 37.9	166 lbs.	200 lbs.

Gas Connection: 3/4" NPT on the right

Clearance for combustible work area: 6" rear & 15" sides

Altitudes over 2,000 feet may need high altitude orifice adjustments to deliver BTU output listed

NOTE: MIGALI® RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE



TOLL FREE: 800.852.5292  
 WEB: www.migali.com




Conforms to ANSI STD Z33  
 11b-2009 (2011), NSF/ANSI STD 4  
 & CSA STD 18-2009(2011)




# DIMENSIONAL DRAWINGS


C-F35









C-F40



C-F50



C-F75



SIDE VIEW



MIGALI® REMAINS AN AMERICAN FAMILY COMPANY SINCE 1955